

Mr./Mrs./Ms.:

Model:

Reg. No.:

Invoice/Job No.:

Odometer Reading:

V.I.N.:



RANGE ROVER SPORT (ALL MODELS ARDUOUS) MAINTENANCE CHECK SHEET

Table with columns for Service type (O, A, B) and rows for Months and .000 km intervals.

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked * Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

Oil OIL SERVICE

- 1. Renew engine oil and filter (Every 3 months / 6,000 Km)
2. Inspect brake pads for wear, calipers for leaks and disks for condition (Every 3 months / 6,000 Km)
3. Inspect road wheel speed sensor harness for damage (Every 3 months / 6,000 Km)
4. Drain fuel sedimentor (Diesel) (Every 3 months / 6,000 Km)
5. Adjust the electric park brake shoes (Every 3 months / 6,000 Km)
6. Check the condition of the electric park brake system (Every 3 months / 6,000 Km)

A B MAIN SERVICE (VEHICLE INTERIOR)

- 7. Check condition and security of seats and seatbelts
8. Check operation of all lamps, horns and warning indicators
9. Check operation of front/rear wipers and washers and condition of wiper blades
10. Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re select HIGH range gears
11. Replace pollen filter

MAIN SERVICE (VEHICLE EXTERIOR)

- 12. Annual corrosion/cosmetic inspection - Using annual corrosion inspection sheet
13. Check tyre pressures, condition and tread depth.
14. Remove road wheels
15. Replace Brake Fluid (Every 2 years)*
16. Renew fuel filter element (Diesel)
17. Install road wheels to opposite sides of the same axle (Use anti-sieze compound on spigot bore) Not vehicles fitted with uni-directional tyres
18. Visually check intercooler/radiator for external obstructions and fan blades for damage. Remove debris with a low pressure hose
19. Renew the air suspension inlet filter
20. Check operation of door checks, bonnet catch & fuel flap and lubricate door checks
21. Apply lubricant to door seals - Russian and Nordic markets only

MAIN SERVICE (UNDER BONNET)

- 22. Check anti-freeze specific gravity
23. Renew coolant (Every 10 years)
24. Renew spark plugs (Vehicles using leaded fuel or low cost spark plugs)
25. Renew spark plugs
26. Renew air cleaner element
27. Clean throttle disc (V8 - Gulf markets only)
28. Check condition of ancillary driving belts
29. Renew ancillary driving belts (Petrol without Dynamic Response)
30. Renew ancillary driving belts (Diesel and Petrol with Dynamic Response)
31. Renew supercharger driving belt (Petrol Supercharged)
32. Renew front and rear camshaft timing belts, tensioners and tensioner bolt (Diesel)

MAIN SERVICE (UNDER BONNET)

- 33. Check/top up brake, PAS, Dynamic Response and clutch fluid levels and screen washer reservoirs
34. Check/top up battery electrolyte level. - low maintenance battery fitted
35. Check battery condition and check/top up battery electrolyte level - low maintenance battery fitted - MENA markets only
36. Clear debris from auxiliary oil cooler (Petrol Supercharged)

A B MAIN SERVICE (UNDER VEHICLE)

- 37. Renew engine oil and filter
38. Renew automatic transmission fluid and filter (Every 10 years)
39. Renew transfer case fluid, replace drain and fill plugs and washers
40. Renew front and rear axle fluid (Every 10 years)
41. Renew locking differential fluid
42. Check for free play in all suspension and body mounting rubbers
43. Check condition of all suspension, driveshafts and steering boots and gaiters
44. Replace all flexible brake hoses (Every 6 years)*
45. Check visually brake servo hose, brake, fuel, PAS, Dynamic Response and clutch pipes, unions and electrical harnesses for chafing, leaks and corrosion
46. Remove any debris from between the Dynamic Response valve block and the integrated body frame
47. Replace Dynamic Response filter in valve block and replace lost fluid
48. Check for fluid leaks
49. Check exhaust system for leaks, security and damage
50. Check steering rod ball joint fixings and condition of ball joints and dust covers
51. Check torque of tie rod end nuts - M12 tie rod end nuts only - 76 Nm
52. Check shock absorbers/height sensors and harness assembly for leakage and damage
53. If fault lamp(s) are illuminated, interrogate that system using T4/IDS and report findings*
54. Carry out road test (see WARNING over page)
55. Reset service interval announcement indicator
56. Endorse service record
57. Check for any applicable outstanding service actions or recalls
58. Report any unusual features of vehicle condition and additional work required

The maintenance items listed, are those recommended for vehicles operating under arduous driving, road and climatic conditions. More frequent attention may be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions, off road driving or frequent towing of trailers. See recommendations on back of sheet. Service check completed, cosmetic/corrosion inspection check completed and service portfolio book endorsed.

Name: Signature: Date:

